

ARTLINES FLEX LVT - Loose Lay

Technical specifications		Artlines Flex	Artlines Flex 0.55
Total Thickness	ISO 24346	5.00 mm	4.00 mm
Thickness of wear layer	ISO 24340	1.00 mm	0.55 mm
Collection size		36	40
Commercial very heavy	EN-ISO 10874	Class 34	Class 33
Light industrial general	EN-ISO 10874	Class 43	Class 42
Tie size	EN-ISO 24342	50 x 50 cm	50 x 50 cm
		75 x 50 cm	75 x 50 cm
			80 x 80 cm
Plank size	EN-ISO 24342	100 x 20 cm	100 x 20 cm
		120 x 20 cm	120 x 20 cm
			150 x 28 cm
Squareness and straightness	EN-ISO 24342	≤ 400 mm: ≤ 0.25 mm	≤ 400 mm: ≤ 0.25 mm
		≥ 400 mm: ≤ 0.35 mm	≥ 400 mm: ≤ 0.35 mm
Total weight	EN-ISO 23997	ca.6550 gr/m ²	ca.5200 gr/m ²
Packaging per carton tiles		50 x 50 cm: 2.5 m ² =10 pcs	50 x 50 cm: 3.0 m ² =12 pcs
		75 x 50 cm: 2.25 m ² =6 pcs	75 x 50 cm: 3.75 m ² =10 pcs
			80 x 80 cm: 160 m ² =250 pcs / pallet
Packaging per carton planks		100 x 20 cm: 2.0 m ² =10 pcs	100 x 20 cm: 2.0 m ² =10 pcs
		120 x 20 cm: 2.4 m ² =10 pcs	120 x 20 cm: 2.4 m ² =10 pcs
Slip resistance	DIN 51130	R10	R10
Acoustical impact noise reduction	EN-IS O 717-2	14 dB	14 dB
Castor chair continuous use	EN 425	No effect	No effect
Indentation-residual	ISO 24343-1 EN 433	≤ 0.12 mm	≤ 0.10 mm
Light fastness	EN ISO 105 B02	≥ 6	≥ 6
Resistance to chemicals	EN-ISO 26987	Very good	Very good
Dimensional stability	EN-ISO 23999	≤ 0.02 %	≤ 0.05 %



ATECO ZEMİN MALZEMELERİ SAN. TİC. LTD. ŞTİ

A: Poligon Mah. Katar Cad. No:21/A

Sarıyer / İstanbul - Türkiye

info@atecozemin.com www.atecozemin.com

T: +90 212 229 1914 pbx F: +90 212 229 4647

Bu ürünler Forbo Hollanda fabrikasında Ateco Zemin için üretilmiştir.